




since
1938

PNEUMA-WRAP™ BRAKE

The ideal machine for forming L, Flat, Wrap, TDC® and TDF® Duct



MACHINE DESIGN:

- Redesigned tooling to accept any size duct from 7" up to standard 5' without adjustment
- Redesigned beam to clear pins on lined duct
- Rugged Welded Steel Construction
- Maintenance-Free Bearing & Guides
- Pneumatic Drive For Clamping Beam with Automatic Return
- Pneumatic Drive For Folding Beam with Automatic Return
- Pneumatic Operated Pedal Control
- Dial-Adjustable Bend Angle 0 to 90°
- Automatic TDC®/F® Notch Locator
- Front Adjustable Support Apron
- Safety Interlock Controls



5480 - Sixth Street S.W. • Cedar Rapids, IA 52404
Email: sales@mestekmachinery.com • Website: mestekmachinery.com
319.364.9181



The FIRST Premier Partner Program Member
to Join this Elite Group

PNEUMA-WRAP™ BRAKE

MACHINE FEATURES:

- Foot Pedal Control
- Pneumatic Drive Folding Beam
- Dial-adjustable Bend angle 0-90
- Safety Interlock Controls
- Maintenance-Free Bearing & Guides
- Automatic TDC® Notch Locator
- Rugged Welded Steel Construction

BEND LENGTH WIDTH:

- 60" (1524mm) maximum

MAX MATERIAL THICKNESS:

- 16 gauge (1.6mm)

MIN WRAP DUCT SIZE:

- 8 ¾" x 8 ¾" (220mm x 220mm)

AIR SUPPLY:

- 11 CFM of Clean/Dry @ 100 PSI (Not to exceed 120 PSI)

WEIGHT:

- 3500 Pounds

SIZE :

- 58.5" x 24" x 41"

